

# PIETBOON

MANUAL  
Carpet TIDE by Carpetlinq

## Congratulations on your purchase!

Every item in the Piet Boon Collection stands out due to its clean, robust design and use of natural, neutral materials. Comfort, sustainability, and a timeless design are our preconditions for every product. Our carpet finishes lend them a deliberately distinguishable character for daily use. We wish you lots of home joy with your purchase.

## Product Specifications

### Materials

The **TIDE** is a hand-tufted rug, available in 50% Bamboo with 50% Eucalyptus. These fibers are products of nature and as with all natural products, a slight deviation in texture and colour may occur between dye lots.

### Maintenance

It's important that rugs are turned regularly, so that the effects caused by light and normal wear might be equivalent in the whole surface of the rug. When there is furniture placed on the rug exercising pressure, a rug protection can be used so it won't damage the pile and the overall look of the product.

Regular cleaning is essential to maintain the appearance of your rug. Use a good vacuum cleaner, which should have 1200W of power and vacuum in the direction of the pile. These rugs must be cleaned regularly. Naturally, lighter rugs need to be cleaned more often than darker ones. Steam cleaning or any other methods which involve a substantial increase of temperature are not recommended. For this collection it is highly recommended a professional injection-extraction method washing with low temperatures and low-pressure values. For a deeper cleaning, please use a specialized rug cleaning company.

### Colours

The natural quality lends each carpet a unique colour. Colour intensity may vary depending on the dye bath. Avoid direct sunlight at all times. Longer exposure to sunlight will cause damage and fading.

### Colour fastness to light

4 - 5

### Colour fastness to water

4 - 5

### Dimension variations

Dimensions may vary up to 3%. Your rug may stretch lightly. This is fully normal.

### Fire Classification

Fire classification - EN 13501-1:2010-Cfl-s1.

### Primary backing

100% Polyester

### Secondary backing

100% Polyester

### Pile weight

5

### Total weight

5,5

### Anti-slip

Anti-slip is available separately in two fixed dimensions, as a roll for installation, or cut to size for this particular carpet.

### Extra information

Do not store this carpet in rolled-up form for longer than 3-4 weeks

### Warranty

Please refer to our regular terms.